

SONO-HAC-T-COMPDS

There's one that's perfect for every application.

MODEL: 3300W 4400E 4400W 4400H 5105E 5105H

Crane Rating (FT/Lbs)	11,500	16,000	16,000	16,000	25,000	25,000
Max. Horizontal Reach (FT)	15'	15' 9"	15' 9"	15' 9"	18' 4"	18' 4"
Angle of Rotation (Degrees)	400	400	400	400	Continuous	Continuous
Boom Elevation Angle	-5° to + 80°	-5° to + 80°	-5° to + 80°	-5° to + 80°	-5° to + 72°	-5° to + 72°
Winch Capacity (Lbs)	1,600	2,200	2,200	2,200	2,640	2,640
Winch Speed (FT per Min)	20	36	25	40	33	33
Non-twisting Cable length (FT)	82	98	98	98	100	100
Non-twisting Cable diameter (Inches)	1/4"	5/16"	5/16"	5/16"	5/16"	5/16"
Non-twist. Cable breaking strength (Lbs)	13,300	13,300	13,300	13,300	13,300	13,300
Crane Weight	530	720	720	700	1,000	1,000
Number of Hydraulic Extensions	1	1	1	1	2	2
Number of Manual Extensions	1	1	1	1	0	0
Gallons per Minute	0.8	1.9	1	2.6	3.2	3.2
Hydraulic Pressure (PSI)	2,300	2,850	2,830	2,830	2,500	2,500

MODEL: 6206H 8805H 9506.2LH 9506.3LH 12006.2LH 12006.3LH

Crane Rating (FT/Lbs)	37,000	52,000	56,000	56,000	67,000	67,000
Max. Horizontal Reach (FT)	21'	22'	22'	27' 3"	22'	27' 6"
Angle of Rotation (Degrees)	Continuous	Continuous	Continuous	Continuous	Continuous	Continuous
Boom Elevation Angle	-5° to + 75°	-10° to + 75°	-10° to + 75°	-10° to + 75°	-10° to + 75°	-10° to + 75°
Winch Capacity (Lbs)	3,100	5,070	5,290	5,290	5,950	5,950
Winch Speed (FT per Min)	46	40	40	40	40	40
Non-twisting Cable length (FT)	100	115	115	115	115	115
Non-twisting Cable diameter (Inches)	25/64"	25/64"	15/32"	15/32"	15/32"	15/32"
Non-twist. Cable breaking strength (Lbs)	20,800	22,500	26,500	26,500	26,500	26,500
Crane Weight	1,280	1,850	1,900	2,020	2,100	2,270
Number of Hydraulic Extensions	2	2	2	3	3	3
Number of Manual Extensions	0	0	0	0	0	0
Gallons per Minute	4.2	5	6	6	7	7
Hydraulic Pressure (PSI)	2,600	2,450	2,700	2,700	2,500	3,000

3300W LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
2	3,200	10	1,150
3	3,200	11	1,040
4	2,850	12	960
5	2,300	14	820
7	1,650	15	750
9	1,280		

4400H LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
2	4,400	10	1,600
3	4,400	11	1,450
4	4,000	12	1,300
5	3,100	14	1,150
7	2,150	15	990
9	1,750		

6206H LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
5	6,200	14	2,450
6	5,500	16	2,300
8	4,400	18	1,800
10	3,600	20	1,700
12	2,900	21	1,660

9506.3LH LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
5	9,500	18	3,100
6	9,300	20	2,800
8	7,050	22	2,550
10	5,600	24	2,300
12	4,650	26	2,150
14	3,900	27' 3"	1,950
16	3,500		

4400E LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
2	4,400	10	1,600
3	4,400	11	1,450
4	4,000	12	1,300
5	3,100	14	1,150
7	2,150	15	990
9	1,750		

5105E LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
3	5,100	11	2,250
5	4,300	12	2,050
7	3,700	14	1,750
9	2,650	16	1,550
10	2,500	18' 4"	1,350

8805H LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
5	8,800	14	3,570
6	8,650	16	3,250
8	6,500	18	2,850
10	5,200	20	2,600
12	4,300	22	2,300

12006.2LH LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
5	11,900	14	4,750
6	9,450	16	4,150
8	8,350	18	3,700
10	6,700	20	3,350
12	5,550	22	2,950

4400W LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
2	4,400	10	1,600
3	4,400	11	1,450
4	4,000	12	1,300
5	3,100	14	1,150
7	2,150	15	990
9	1,750		

5105H LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
3	5,100	11	2,250
5	4,300	12	2,050
7	3,700	14	1,750
9	2,650	16	1,550
10	2,500	18' 4"	1,350

9506.2LH LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
5	9,500	14	3,900
6	9,300	16	3,500
8	7,050	18	3,100
10	5,600	20	2,800
12	4,650	22	2,550

12006.3LH LIFTING CAPACITIES

FEET	LBS.	FEET	LBS.
5	11,900	18	3,700
6	9,450	20	3,350
8	8,350	22	2,900
10	6,700	24	2,700
12	5,550	26	2,550
14	4,600	27' 6"	2,300
16	4,200		

Configurable to meet many requirements. Structures are designed for a normal working life of 15 years.